



The SRS lets you take advantage of a spray that provides the unrivaled degree of Hunter quality no matter what nozzle you currently have in stock. Better yet, choose from a wide selection of fixed and adjustable arc nozzles Hunter offers for use with the SRS. Either way, you'll receive a superior spray. One whose construction, highlighted by a rugged flat body cap, is both

brawny and durable. And one whose performance delivers the most effective coverage possible, thanks to a no-flow-by wiper seal that allows your system to handle low water pressure as proficiently as high. And, best of all, what truly makes this spray head so hard to resist is that its price is so easy to handle.

Features & Benefits



Rugged body cap design

Stands up to heavy traffic in public areas

Compatible with all standard nozzles

Accepts popular female-threaded nozzles including Hunter adjustable arc nozzles

Heavy-duty UV-resistant wiper seal

Assures long life at a wide range of water pressures

Standard side inlet

Featured on 15 and 30 cm models for installation convenience

Ratcheting riser for quick arc alignment

Ensures quick pattern alignment

Strong stainless steel spring

Ensures reliable retraction year after year



Hunter nozzles are color-coded for quick and easy radius identification.

Models

- SRS-00 – Shrub
- SRS-02 – 5 cm Pop-up
- SRS-03 – 7.5 cm Pop-up
- SRS-04 – 10 cm Pop-up
- SRS-06 – 15 cm Pop-up
- SRS-12 – 30 cm Pop-up

Dimensions

- Overall height:
 - SRS-02 – 10 cm
 - SRS-03 – 12.5 cm
 - SRS-04 – 15 cm
 - SRS-06 – 21.5 cm
 - SRS-12 – 39 cm
- ½" female inlet NPT
- Exposed diameter: 5 cm

Operating Specifications

- Recommended pressure range: 1.0 to 4.8 bars; 103 to 482 kPa
- Flow-by: .7 bars; 68 kPa or greater; 0.02 m³/hr; 0.4 l/min otherwise
- Precipitation rates: approximately 3.8 cm per hour

SPECIFICATION GUIDE

EXAMPLE: **SRS - 04 - 10H**

MODEL	POP-UP HEIGHT	NOZZLE SERIES	PATTERN
SRS	00 = Shrub 02 = 5 cm Pop-up 03 = 7.5 cm Pop-up 04 = 10 cm Pop-up 06 = 15 cm Pop-up 12 = 30 cm Pop-up	8 = 8 Series 10 = 10 Series 12 = 12 Series 15 = 15 Series 17 = 17 Series	A = Adjustable Q = Quarter-Circle H = Half-Circle F = Full-Circle

Note: Bodies and nozzles sold separately. Also compatible with Hunter's bubbler and specialty nozzles.

Adjustable Arc Nozzles Performance Data – Metric

Arc	Pressure Bars kPa	2.4 Meter Radius (8 ft.) Adjustable from 25° to 360° Trajectory: 0° Color Code: Brown ●					3.0 Meter Radius (10 ft.) Adjustable from 25° to 360° Trajectory: 15° Color Code: Red ●					3.7 Meter Radius (12 ft.) Adjustable from 25° to 360° Trajectory: 28° Color Code: Green ●					4.6 Meter Radius (15 ft.) Adjustable from 25° to 360° Trajectory: 28° Color Code: Black ●					5.2 Meter Radius (17 ft.) Adjustable from 25° to 360° Trajectory: 28° Color Code: Gray ●										
		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle										
		8A	8A	10A	10A	12A	12A	15A	15A	17A	17A	8A	8A	10A	10A	12A	12A	15A	15A	17A	17A	8A	8A	10A	10A	12A	12A	15A	15A	17A	17A	
	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip		
	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr		
45°	1.4	137	2.1	0.04	0.6	68	78	2.7	0.04	0.6	41	47	3.4	0.06	0.9	40	47	4.2	0.09	1.5	38	44	4.8	0.11	1.8	37	43	5.2	0.13	2.1	38	44
	1.7	171	2.4	0.04	0.7	60	69	3.0	0.04	0.7	44	44	3.7	0.06	1.0	37	43	4.5	0.10	1.6	37	43	5.2	0.11	2.1	38	44	5.2	0.13	2.1	38	44
	2.1	206	2.4	0.06	0.9	75	86	3.0	0.06	0.9	55	55	3.7	0.07	1.2	43	49	4.5	0.11	1.8	40	47	5.2	0.14	2.3	41	47	5.2	0.14	2.3	41	47
	2.4	240	2.7	0.06	1.0	62	71	3.3	0.06	1.0	48	48	4.0	0.08	1.4	42	49	4.8	0.12	1.9	39	45	5.5	0.14	2.4	38	44	5.5	0.14	2.4	38	44
	2.7	274	3.0	0.08	1.4	71	82	3.6	0.08	1.4	57	57	4.3	0.10	1.6	42	48	5.2	0.13	2.1	38	44	5.8	0.16	2.6	37	43	5.8	0.16	2.6	37	43
90°	1.4	137	2.1	0.08	1.3	68	78	2.7	0.08	1.3	47	47	3.4	0.11	1.9	40	47	4.2	0.17	2.9	38	44	4.8	0.22	3.7	37	43	5.2	0.27	4.5	41	47
	1.7	171	2.4	0.09	1.5	60	69	3.0	0.09	1.5	44	44	3.7	0.12	2.1	37	43	4.5	0.20	3.3	37	43	5.2	0.26	4.3	38	44	5.2	0.26	4.3	38	44
	2.1	206	2.4	0.11	1.9	75	86	3.0	0.11	1.9	55	55	3.7	0.14	2.4	43	49	4.5	0.21	3.5	40	47	5.2	0.27	4.5	41	47	5.2	0.27	4.5	41	47
	2.4	240	2.7	0.12	1.9	62	71	3.3	0.12	1.9	48	48	4.0	0.17	2.8	42	49	4.8	0.23	3.9	39	45	5.5	0.28	4.7	38	44	5.5	0.28	4.7	38	44
	2.7	274	3.0	0.17	2.8	71	82	3.6	0.17	2.8	57	57	4.3	0.19	3.2	42	48	5.2	0.26	4.3	38	44	5.8	0.31	5.2	37	43	5.8	0.31	5.2	37	43
120°	1.4	137	2.1	0.10	1.7	68	78	2.7	0.10	1.7	47	47	3.4	0.15	2.5	40	47	4.2	0.23	3.9	38	44	4.8	0.29	4.9	37	43	5.2	0.36	6.1	41	47
	1.7	171	2.4	0.12	2.0	60	69	3.0	0.12	2.0	44	44	3.7	0.17	2.8	37	43	4.5	0.26	4.3	37	43	5.2	0.34	5.7	38	44	5.2	0.34	5.7	38	44
	2.1	206	2.4	0.15	2.5	75	86	3.0	0.15	2.5	55	55	3.7	0.19	3.2	43	49	4.5	0.28	4.7	40	47	5.2	0.36	6.1	41	47	5.2	0.36	6.1	41	47
	2.4	240	2.7	0.15	2.6	62	71	3.3	0.15	2.6	48	48	4.0	0.22	3.7	42	49	4.8	0.31	5.2	39	45	5.5	0.38	6.3	38	44	5.5	0.38	6.3	38	44
	2.7	274	3.0	0.22	3.7	71	82	3.6	0.22	3.7	57	57	4.3	0.25	4.2	42	48	5.2	0.34	5.7	38	44	5.8	0.42	7.0	37	43	5.8	0.42	7.0	37	43
180°	1.4	137	2.1	0.15	2.6	68	78	2.7	0.15	2.6	47	47	3.4	0.23	3.8	40	47	4.2	0.35	5.8	38	44	4.8	0.44	7.3	37	43	5.2	0.54	9.1	41	47
	1.7	171	2.4	0.18	3.0	60	69	3.0	0.18	3.0	44	44	3.7	0.25	4.2	37	43	4.5	0.39	6.5	37	43	5.2	0.51	8.6	38	44	5.2	0.51	8.6	38	44
	2.1	206	2.4	0.22	3.7	75	86	3.0	0.22	3.7	55	55	3.7	0.29	4.8	43	49	4.5	0.42	7.0	40	47	5.2	0.54	9.1	41	47	5.2	0.54	9.1	41	47
	2.4	240	2.7	0.23	3.9	62	71	3.3	0.23	3.9	48	48	4.0	0.33	5.5	42	49	4.8	0.47	7.8	39	45	5.5	0.57	9.5	38	44	5.5	0.57	9.5	38	44
	2.7	274	3.0	0.33	5.5	71	82	3.6	0.33	5.5	57	57	4.3	0.38	6.4	42	48	5.2	0.51	8.6	38	44	5.8	0.63	10.4	37	43	5.8	0.63	10.4	37	43
240°	1.4	137	2.1	0.21	3.4	68	78	2.7	0.21	3.4	47	47	3.4	0.30	5.0	40	47	4.2	0.47	7.8	38	44	4.8	0.59	9.8	37	43	5.2	0.73	12.1	41	47
	1.7	171	2.4	0.24	3.9	60	69	3.0	0.24	3.9	44	44	3.7	0.33	5.6	37	43	4.5	0.52	8.7	37	43	5.2	0.68	11.4	38	44	5.2	0.68	11.4	38	44
	2.1	206	2.4	0.30	4.9	75	86	3.0	0.30	4.9	55	55	3.7	0.38	6.4	43	49	4.5	0.56	9.4	40	47	5.2	0.73	12.1	41	47	5.2	0.73	12.1	41	47
	2.4	240	2.7	0.31	5.1	62	71	3.3	0.31	5.1	48	48	4.0	0.44	7.4	42	49	4.8	0.62	10.4	39	45	5.5	0.76	12.6	38	44	5.5	0.76	12.6	38	44
	2.7	274	3.0	0.44	7.4	71	82	3.6	0.44	7.4	57	57	4.3	0.51	8.5	42	48	5.2	0.68	11.4	38	44	5.8	0.84	13.9	37	43	5.8	0.84	13.9	37	43
270°	1.4	137	2.1	0.23	3.9	68	78	2.7	0.23	3.9	47	47	3.4	0.34	5.7	40	47	4.2	0.52	8.7	38	44	4.8	0.66	11.0	37	43	5.2	0.77	12.8	38	44
	1.7	171	2.4	0.27	4.4	60	69	3.0	0.27	4.4	44	44	3.7	0.37	6.2	37	43	4.5	0.59	9.8	37	43	5.2	0.77	12.8	38	44	5.2	0.77	12.8	38	44
	2.1	206	2.4	0.33	5.6	75	86	3.0	0.33	5.6	55	55	3.7	0.43	7.2	43	49	4.5	0.63	10.6	40	47	5.2	0.82	13.6	41	47	5.2	0.82	13.6	41	47
	2.4	240	2.7	0.35	5.8	62	71	3.3	0.35	5.8	48	48	4.0	0.50	8.3	42	49	4.8	0.70	11.7	39	45	5.5	0.85	14.2	38	44	5.5	0.85	14.2	38	44
	2.7	274	3.0	0.50	8.3	71	82	3.6	0.50	8.3	57	57	4.3	0.57	9.5	42	48	5.2	0.77	12.8	38	44	5.8	0.94	15.7	37	43	5.8	0.94	15.7	37	43
360°	1.4	137	2.1	0.31	5.1	68	78	2.7	0.31	5.1	47	47	3.4	0.45	7.6	40	47	4.2	0.70	11.7	38	44	4.8	0.88	14.7	37	43	5.2	1.09	18.2	41	47
	1.7	171	2.4	0.35	5.9	60	69	3.0	0.35	5.9	44	44	3.7	0.50	8.3	37	43	4.5	0.78	13.0	37	43	5.2	1.03	17.1	38	44	5.2	1.03	17.1	38	44
	2.1	206	2.4	0.44	7.4	75	86	3.0	0.44	7.4	55	55	3.7	0.57	9.5	43	49	4.5	0.84	14.1	40	47	5.2	1.09	18.2	41	47	5.2	1.09	18.2	41	47
	2.4	240	2.7	0.46	7.7	62	71	3.3	0.46	7.7	48	48	4.0	0.66	11.1	42	49	4.8	0.94	15.6	39	45	5.5	1.14	18.9	38	44	5.5	1.14	18.9	38	44
	2.7	274	3.0	0.66	11.1	71	82	3.6	0.66	11.1	57	57	4.3	0.76	12.7	42	48	5.2	1.03	17.1	38	44	5.8	1.25	20.9	37	43	5.8	1.25	20.9	37	43

Note: The Institutional Spray's built-in pressure regulation controls output to a maximum of 2.1 Bars (206 kPa).

Pro-Spray® Nozzles Performance Data – Metric

Arc	Pattern	Pressure Bars kPa	2.4 Meter Radius (8 ft.) Fixed (Quarter, Half, Full) Trajectory: 0° Color Code: Brown ●					3.0 Meter Radius (10 ft.) Fixed (Quarter, Half, Full) Trajectory: 15° Color Code: Red ●					3.7 Meter Radius (12 ft.) Fixed (Quarter, Half, Full) Trajectory: 28° Color Code: Green ●					4.6 Meter Radius (15 ft.) Fixed (Quarter, Half, Full) Trajectory: 28° Color Code: Black ●					5.2 Meter Radius (17 ft.) Fixed (Quarter) Trajectory: 28° Color Code: Gray ●										
			Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle		Nozzle								
			8	8	10	10	12	12	15	15	17	17	8	8	10	10	12	12	15	15	17	17	8	8	10	10	12	12	15	15	17	17	
		Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip	Radius	Flow	Flow	Precip	Precip		
		m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr	m	m ³ /hr	l/min	mm/hr	mm/hr		
90°	Q	1.4	137	2.1	0.04	0.6	34	39	2.7	0.07	1.1	36	42	3.4	0.11	1.9	40	47	4.2	0.17	2.9	38	44	4.9	0.22	3.7	37	43	5.2	0.26	4.3	38	44
		1.7	171	2.4	0.04	0.7	29	34	3.0	0.07	1.3	37	44	3.7	0.12	2.1	37	43	4.5	0.20	3.3	37	43	5.2	0.26	4.3	38	44	5.2	0.26	4.3	38	44
		2.1	206	2.4	0.05	0.9																											